

MAIN LOAD LINE

P/N: GC01-000-00-00



FEATURES

- ½" Drop-forged O-rings and captive-eye snap link
- Stainless steel swivel w/permanently lubricated thrust bearings
- Weighted anti-whipping bag

TECHNICAL

- Weight: 32 – 38 lbs. (14.5 – 17.2 kg.) depending on length (includes weight bag)
- Rated load: 600 lbs. (272 kg.)

MATERIAL

- ½" High Molecular Weight Polyethylene Spectra® multi-filament core
- Braided polyester cover with high-vis urethane coating

ABOUT

Emergco's Main Load Line assembly is constructed of a SPECTRA® multi-filament fibre core and a braided polyester cover with a high visibility urethane coating, giving a firm, abrasive resistant, low elongation rope with a minimum tensile strength of 13,000 lbs.

Load line ends are terminated with eye thimbles and are fitted on one end with a drop forged steel 0.5" 3" inside diameter "O-ring", and on the other end with a drop forged steel auto locking captive eye snap-link.

The assembly includes a stainless steel swivel with permanently lubricated thrust bearings to control torque forces and prevent kinking of the load line(s) suspension assembly.

- Fully-approved, field proven fixed line solution from the industry leader in Human External Cargo (HEC).
- High-visibility braided polyester cover protects rope core from ingress of abrasive material and UV radiation
- Stainless swivel ensures line does not become twisted or kinked
- Weighted anti-whipping bag for empty-line flight dynamics

